TMT120 Temperature Transmitter

| Temperature Transmitter | | | | TMT120 |) | | | Α | Α | | | | | | | Pric |
|----------------------------|--|--------------------------|--------------|--------|---|---|---|---|---|-----|---|------|---|-----|-----------|------|
| Measurement type | Temperature | (HMP110T) | | | Α | | 7 | Ť | † | t | T | 7 | 寸 | | \dagger | 1 |
| Probe details | Wall mount/fixed probe HMP110T A | | | | | | | | | | | | | | | |
| | Remote probe with 3 m cable | | | | | | | | | | | | | | | |
| | Remote probe with 5 m cable | | | | | | | | | | | | | | | |
| | Remote probe with 10 m cable | | | | | | | | | | | | | | | |
| | Remote probe with 10 m cable + 10 m extension | | | | | | | | | | | | | | | |
| | Remote probe with 20 m cable | | | | | | | | | | | | | | | |
| | Remote probe with 1.2 m cable | | | | | | | | | | | | | | | |
| Display Output signal | No display | | | | | | 0 | | | | | | | | | |
| | Display 1 1 | | | | | | | | | | | | | | | |
| | No Display, no logo 420 mA 2-wire loop-powered A | | | | | | | | | | | | | | | |
| Output signal | 420 MA | 2-wire loop-pov | verea | | | | | A | | | | | | | | |
| Parameter for Output 1 | T | -40+60 °C | (-40+140 °F) | | | | | E | | | | | | | | |
| | | -20+80 °C | (-4+176 °F) | | | | | C | | | | | | | | |
| | | 0+60 °C | (+32+140 °F) | | | | | _ | | | | | | | | |
| | | -40+80 °C | (-40+176 °F) | | | | | E | | | | | | | | |
| | 0 | 0+50 °C | (+32+122 °F) | | | | | F | | | | | | | | |
| SPECIAL | Quantity | Т | Scale | _ | | | | X | | | | | | | | |
| Parameter for Output 2 | None | | | | | | | | Α | | | | | | | |
| Display Units | Metric 1 | | | | | | | | | | | | | | | |
| Sensor protection | Non metric 2 | | | | | | | | | | | | | | | |
| | Plastic grid (for HMP110T) | | | | | | | | | - 1 | | | | | | |
| | Plastic grid with PTFE filter (for HMP110T) | | | | | | | | | | | | | | | |
| | - · · · · · · · · · · · · · · · · · · · | | | | | | | | 3 | | | | | | | |
| | | d filter for HMP110T | DRW244938 | BSP | | | | | | | Ε | | | | | |
| Transmitter installation | No accessorie | | | | | | | | | | | Α | | | | |
| | | th installation kit (215 | 5109) | | | | | | | | | С | | | | |
| Installation kit for probe | No accessorio | | | | | | | | | | | | 1 | | | |
| | Duct installation kit (215619) | | | | | | | | | | 2 | | | | | |
| | Probe mounting flange (226061) | | | | | | | | | | | 3 | | | | |
| | Outdoor installation: DTR504A Radiation Shield with probe installation kit (DTR504A) | | | | | | | | |) | | 5 | | | | |
| | Probe mounting clamp, 1 piece (225501) | | | | | | | | | | 6 | | | | | |
| Cable bushings | Cable gland f | or 26 mm diamete | er cable | | | | | | | | | | | Α | | |
| | Conduit fitting PG9 | | | | | | | | | | В | | | | | |
| | Conduit fitting NPT 1/2" | | | | | | | | | С | | | | | | |
| | No bushing (rubber plug) | | | | | | | | | | D | | | | | |
| | All bushings (includes A, B, C and D) | | | | | | | | | | Z | | | | | |
| PC Accessories | No | | | | | | | | | | | | | _ (| ן כ | |
| | Service cable | for PC, USB (219685 | 5) | | | | | | | | | | | | 1 | |
| Operation manual | No manual | | | | | _ | | | - | | | | _ | | Α | |
| | Multilingual | | | | | | | | | | | | | | Z | |
| | | | | | | | | | | | | Tota | | | | |
| | | | | | | | | | | | | QT\ | | | | |
| | | | | | | | | | | | | | | -1 | | |

Selections in bold are included in the prices of the basic versions

Selections in italic are available at an extra cost

Example of order code with typical settings

TMT120 A A O A B A 1 1 A 1 A 0 Z

Total value